

DAFA Butyl 200 joint sealant

DAFA Butyl 200 is a non-hardening joint sealant used for sealing in various constructions.

Description

Butyl 200 is a non-hardening joint sealant used for sealing in a range of structures.

Application

For sealing purposes on a wide range of structures, where the butyl is applied in a "tight fit joint". This means areas where there is a form of mechanical fixing (e.g. between a concrete floor and a floor still). Used for instance in overlapping joints in moulding for caravans and for sealing joints in roof structures.

Properties

- Color: light grey
- Good UV-resistance
- Good resistance against acids and alkalis.
- The surface must be kept clean, dry and free of oil and grease.
- Can be stored for up to one year (in a dry, cool and frost-free environment)

Please contact our customers service department for further information on +45 87 47 66 66



Type/contents	Contents per box	DAFA item no	EAN no
Tube, 310 ml.	25 tubes	233400100	5705636098944
Pose 600 ml.	11 bags	620010694	5705636313764

Technical specifications

Material	Non-hardening butyl joint sealant
Temperature resistance	-40 °C to + 80 °C
Installation temperature	+5 °C to +30 °C
Storage	1 year. Store in a dry, cool and frost-free environment
Density	1,6g/cm ³
Resistance	Good UV-resistance. Good resistance against acids and alkalis
Color	Light grey

